

DECLARATION OF PERFORMANCE

IN ACCORDANCE WITH CONSTRUCTION PRODUCTS REGULATION (EU) NO. 305/2011 & 574/2014
 AND
 IN ACCORDANCE WITH THE SWISS CONSTRUCTION PRODUCTS LAW 933.0

DoP-No. 410-420-460-470 / CPR / 30.10.2019

- Unique identification code of the product type:
Multi-layer parquet elements according to EN 13489:2002 (wood flooring)
Unopark / Megapark / Megapark Langstab / Trendpark / Trendpark Flow Edition / Master Edition (Studiopark and Silverlinedimension) / Silverline Edition / Formpark / Formpark Quadrato
- Intended use(s) of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Floor covering for indoor use (to fully bond on substrate)
- Name, registered trade name or registered trade mark and contact adress of the manufacturer in accordance with Article 11, paragraph 5:
Bauwerk Parkett AG Neudorfstrasse 49 CH-9430 St. Margrethen
- System or systems of assessment and verification of constancy of performance of the construction products as set out in Annex V:
System 3
- In case of a declaration of performance concerning a construction product covered by a harmonised standard:
EN 14342:2013

regarding Formaldehyde- and Pentachlorphenole:	regarding reaction of fire:		
eph - Entwicklungs- und Prüflabor Holztechnologie Zellescher Weg 24 D-01227 Dresden (not. body 0766) or eco-INSTITUT GmbH Schanzenstraße 6 – 20 D-51063 Köln (not. Body 2097)	ÖTI – Institut für Ökologie, Technik und Innovation A-1050 Wien (not. body 0534)	eph - Entwicklungs- und Prüflabor Holz- technologie Zellescher Weg 24 D-01227 Dresden (not. body 0766)	IBS Ges.m.b.H Petzoldstr. 45 A-4017 Linz (not. body 1322)

regarding slip-resistance feature:			
eph - Entwicklungs- und Prüflabor Holztechnologie Zellescher Weg 24 D-01227 Dresden (not. body 0766)			

6. Declared performance

Essential characteristics	Performance
Reaction of fire	C_f-s1 (Not burnable subfloors of euroclass A1fl or A2fl with a density of at least 1350 kg/m ³) (only TK Flow Edition, UP Acacia natural oiled, Unopark oak 13mm) D_f-s1
Emission of Formaldehyde	class E1
Content of Pentachlorphenol	≤5 ppm
Breaking strength	NPD
Slip resistance	43 USRV (lacquered) 71 / 60 / 54 USRV (natural oiled: sanded / brushes / deep brushed) 44 / 39 USRV (matt lacquered: sanded / brushed) 99 / 94 USRV (B-Protect: sanded / brushed)
Thermal conductivity	~ 0.14 W / m²K
Biological durability	Use class 1

7. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Christian Steiner, Director Total Quality Management Bauwerk Boen Group

St. Margrethen, 30.10.2019

(Handwritten signature)

 i.v.

BAUWERK®
Parkett

Bauwerk Parkett AG
 CH-9430 St. Margrethen
 info@bauwerk.com
 www.bauwerk-parkett.com